





ACCURACY OF UNDERGROUND SERVICES INFORMATION

UNDERGROUND SERVICES SHOWN ON THIS PLAN HAVE BEEN LOCATED TO THE QUALITY LEVEL INDICATED IN THE LINE
TYPE DESCRIPTOR. THE LOCATION AND DEPTHS STATED SHOULD BE TREATED AS APPROXIMATE AND CAN ONLY BE
VERIFIED VIA PROVING METHODS (MANUAL EXPOSURE/NON-DESTRUCTIVE DIGGING; QL-A) OF WHICH, UNLESS
OTHERWISE AGREED UPON, IS THE RESPONSIBILITY OF THE CONTRACTOR. THERE IS NO GUARANTEE ALL SERVICES THAT EXIST IN THE AREA COVERED ON THIS PLAN ARE SHOWN.
THIS PLAN DOES NOT REPLACE BEFORE YOU DIG PLANS

- OPT(B) - OPTUS ----T(B)---- TESLTRA

----VTC(B)---- VICTRACK COMMS —— AG(B) —— AGGI DRAIN — CSW(B) — CHARGED STORM WATER --- PSW(B) --- PUMPED STORM WATER ----SW(B)---- STORM WATER —— CP(B) —— CATHODIC PROTECTION —— EW(B) —— EARTH WIRE —— EF(B) —— ELECTRIC FENCE — ELV(B) — EXTRA LOW VOLTAGE

— ICW(B) — IRRIGATION CONTROL WIRE ---- LV(B) ---- LOW VOLTAGE ELECTRICITY ----LVO----- LOW VOLTAGE OVERHEAD ——SIG(B)—— RAIL SIGNALS ---VTE(B)--- VICTRACK ELECTRICITY —— CA(B) —— COMPRESSED AIR —— F(B) —— FUEL

—— G(B) —— GAS — GTX(B) — GAS TRANSMISSION ---- O(B) ---- OIL —— SL(B) —— STEAM LINE ---- UKN---- UNKNOWN

— EFF(B) — EFFLUENT —— S(B) —— SEWER —— SRM(B) —— SEWER RISING MAIN ── TRW(B) ── TRADE WASTE

—— DW(B) —— DAM WATER ---- PF(B) ---- POOL FILTRATION ----RW(B) ----- RECYLCED WATER ---- IW(B) ---- IRRIGATION WATER — FS(B) — FIRE SERVICE —— // —— FENCE

> STORM WATER FEATURE ELECTRICAL FEATURE HYDROCARBONS FEATURE UNKNOWN FEATURE SEWER FEATURE POTABLE WATER FEATURE TANK WATER FEATURE BORE WATER FEATURE DAM WATER FEATURE POOL FILTRATION FEATURE RECYCLED WATER FEATURE IRRIGATION WATER FEATURE FIRE SERVICE FEATURE SURVEY MARK / TBM

COMMUNICATIONS FEATURE

600ø PIPE DIAMTER IN MM CL COVER LEVEL INVERT LEVEL DTC DEPTH TO COVER DTI DEPTH TO INVERT BELOW SURFACE LEVEL AUSTRALIAN HEIGHT DATUM AHD BOK BACK OF CURB EOT END OF TRACE

DEPTH BELOW SURFACE (m)

UTL UNABLE TO LOCATE

UTO UNABLE TO OPEN

13.603 POINT LEVEL (AHD)

NTF

-0.55

Where the whole line segment cannot be verified by line of sight, quality Level A shall not be attributed to the line segment between validated points. Quality levels may vary on separate sections of a single subsurface utility, depending on the source information available for each section. NOT TRACED FURTHER

underground service is made from non conductive material such as polyvinyl chloride (pvc) or polyethylene (poly) etc and where the service is also under pressure i.E., cannot be opened or accessed like a conduit or drainage pipe. Examples of these are pvc water pipes, poly irrigation pipes, poly gas pipes, sealed and flooded gravity fed storm water harvesting systems and pressurised rising sewer mains. Without the presence of an accessible trace wire, accurate plans or

capability to isolate and access the service, ability to locate these services is limited. 2. NFORMATION REGARDING UNDERGROUND SERVICE DEPTHS. Depths of services provided on this drawing are obtained using electronic detection (ql-b) unless otherwise stated. Accuracy of these readings is highly dependent on the environment. Depths should be taken as a guide only and service depths should be proven manually on site when excavating within the vicinity of the service. 3. INFORMATION REGARDING DEPTHS OF STORM WATER AND SEWER PIPES. Depths of storm water and sewer pipes are provided in various manors on this plan. Unless otherwise stated, depths of pipes (measured from pit access

points/man holes) are noted from top of pit to pipe invert level (il) in mm. In some cases australia height datum (ahd) levels are provided. This can be used to derive the il/ahd of the pipe. In some cases this may already be calculated and noted as x.Xxil/ahd. 4. METHODS OF OBTAINING DEPTHS FOR STORM WATER & SEWER:

depth measured using electronic detection: the method of determining the il at specific points along any given pipe is obtained using electronic detection. An in-depth explanation of how this is achieved is as follows; a tracing rod is fed into the pipe from an access point, for example a junction pit or manhole. The tracing rod has a locating sonde attached to the head. The rod is fed into the pipe so the head is directly below the specific point with the transmitting sonde sitting on the bottom of the inside of the pipe. Electronic depth is obtained and noted at approximately xmm below the surface level. Additionally if required and if not already provided, surface levels are then measured using a topcon roving surveyor's gps. Electronic depth is then subtracted from the measured gps surface level and to ascertain an approximate invert level and. depth measured using inferred depth: this method assumes consistent and linear fall on a pipe. First, depth is obtained using depths measured at access points for the pipe, for example at 2 separate junction pits or manholes. Approximate depth can then be derived for a particular point along the pipe by considering calculated grade, invert levels and surface level and at the given point.

We are not licensed surveyors therefore certified levels can only be attained by exposing the utility by excavation and having it surveyed by a licensed surveyor. Depending on the nature of the works, reason for survey and field conditions determines if and what method will be used and how much information is provided. Every attempt will be made to provide all relevant information however, should additional information be required subsequent site visits and/or techniques may be needed.

Notes regarding quality levels, taken from as/nzs 5488 2013 quality level is defined as "a classification reflecting the precision and accuracy of utility location and attribute information."

quality levels will be represented on the line type as a single letter (a,b,c or d) in brackets proceeding the utility descriptor. See below. LV(A) — Quality Level A – potholing to prove a utility location.

LV(B) — Quality Level B – use of locating equipment/electronic detection to locate a utility. LV(C) — Quality Level C – using features above the surface to make alignments. For example, fire hydrants, utility pits. ______ LV(D) _____ Quality Level D - from plans, anecdotal evidence.

NOTE This master plan is based on data collected from various surveys conducted across the college over an extended period. While an area may indicate the presence of certain services, it may not necessarily reflect all the services present in that area – there may be additional

services not shown. The focus should be on the idea that "this service has been located and mapped," rather than thinking "this area has been scanned."

DEPTHS STATED SHOULD BE TREATED AS APPROXIMATE AND CAN ONLY BE VERIFIED VIA PROVING METHODS (MANUAL EXPOSURE/NON-DESTRUCTIVE DIGGING; QL-A) OF WHICH, UNLESS OTHERWISE AGREED UPON, IS THE RESPONSIBILITY OF THE
CONTRACTOR.
THERE IS NO GUARANTEE ALL SERVICES THAT EXIST IN THE AREA COVERED ON THIS PLAN ARE SHOWN.

UNDERGROUND SERVICES (PARTIAL) SITE ADDRESS SALESIAN COLLEGE SUNBURY 1 MACEDON ST, SUNBURY VIC 3429

SCALE 1:150 @ A1

PROJECTION: MGA2020 MGA ZONE 55 HEIGHT DATUM: AHD FIELD WORK: JAKE SUTHERLAND DRAWN: JAKE SUTHERLAND DATE: VARIOUS - SEE COVERSHEET

