ELECTRICAL CONSUMERS MAINS CABLE LOCATION

CABLE DETAIL: _____

C(B)	GENERAL COMMUNICATIONS	LE(B)	LIGHTING ELECTRICITY	IW(B)	IRRIGATION WATER	?	UNKNOWN	BSL	BELOW SURFACE LEVEL	SS	SUBSTATION	IC	IRRIGATION CONTROLLER
FO(B)	GENERAL FIBRE OPTIC	LV(B)	LOW VOLTAGE ELECTRICITY	FS(B)	FIRE SERVICE	GPR	GROUND PENERTRATING RADAR	AHD	AUSTRALIAN HEIGHT DATUM	T	TRANSFORMER	SH	SPINKLER HEAD (IRRIGATION)
NBN(B)	NBN	LVO	LOW VOLTAGE ELEC OVERHEAD	SL(B)	STEAM LINE	CA(B)	COMPRESSED AIR	BOK	BACK OF CURB	JP	ELEVATED JOIN (TELSTRA)	ORG	OVERFLOW RELIEF GULLY
OPT(B)	OPTUS	VRE(B)	VICROADS ELECTRICITY	S(B)	SEWER	//	FENCE	COL	CHANGE OF LEVEL	TP	TEST POINT	BT	BOUNDARY TRAP
T(B)	TESLTRA	VTE(B)	VICTRACK ELECTRICITY	SRM(B)	SEWER RISING MAIN	EF(B)	ELECTRIC FENCE	EOT	END OF TRACE	T	TAP	IS IS	INSPECTION SHAFT
VRC(B)	VICROADS COMMS	SIG(B)	RAIL SIGNALS	TW(B)	TRADE WASTE			0.55	DEPTH BELOW SURFACE (m)	WM WM	WATER METER/GAS METER	DP	DOWNPIPE (STORM WATER)
VTC(B)	VICTRACK COMMS	G(B)	GAS	SW(B)	STORM WATER	△	TBM	×13.603	AUSTRALIAN HEIGHT DATUM	V V	VALVE		
EW(B)	EARTH WIRE	GTX(B)	GAS TRANSMISSION	CSW(B)	CHARGED STORM WATER	600ϕ	PIPE DIAMTER IN MM	EJ	ELEVATED JOIN (TELSTRA)	FP	FIRE PLUG		
HV(B)	HIGH VOLTAGE ELECTRICITY	P(B)	PRODUCT LINES AND PIPELINES	AG(B)	AGGI DRAIN	IL	INVERT LEVEL	MP	MARKER POST	FH	FIRE HYDRANT		
HVO	HIGH VOLTAGE ELEC OVERHEAD	W(B)	POTABLE WATER	CP(B)	CATHODIC PROTECTION	CL	COVER LEVEL	LP	LIGHT POLE	HR	HOSE REEL		
IE(B)	IRRIGATION ELECTRICITY	RW(B)	RECYCLED WATER	E(B)	ELECTROLYSIS	DTI	DEPTH TO INVERT	SB	SWITCHBOARD	HB	HYDRANT BOOSTER		

NOTES REGARDING QUALITY LEVELS, TAKEN FROM AS/NZS 5488 2013

QUALITY LEVEL IS DEFINED AS "A CLASSIFICATION REFLECTING THE PRECISION AND ACCURACY OF UTILITY LOCATION AND ATTRIBUTE INFORMATION."

QUALITY LEVELS WILL BE REPRESENTED ON THE LINE TYPE AS A SINGLE LETTER (A,B,C OR D) IN BRACKETS PROCEEDING THE UTILITY DESCRIPTOR. SEE BELOW.

- LV(A) — QUALITY LEVEL A - POTHOLING TO PROVE A UTILITY LOCATION.
- LV(B) — QUALITY LEVEL B - USE OF LOCATING EQUIPMENT/ELECTRONIC DETECTION TO LOCATE A UTILITY.
- LV(C) — QUALITY LEVEL C - USING FEATURES ABOVE THE SURFACE TO MAKE ALIGNMENTS. FOR EXAMPLE, FIRE HYDRANTS, UTILITY PITS.
- LV(D) — QUALITY LEVEL D - FROM PLANS, ANECDOTAL EVIDENCE.

WHERE THE WHOLE LINE SEGMENT CANNOT BE VERIFIED BY LINE OF SIGHT, QUALITY LEVEL A SHALL NOT BE ATTRIBUTED TO THE LINE SEGMENT BETWEEN VALIDATED POINTS.
QUALITY LEVELS MAY VARY ON SEPARATE SECTIONS OF A SINGLE SUBSURFACE UTILITY, DEPENDING ON THE SOURCE INFORMATION AVAILABLE FOR EACH SECTION.

0 4m 8m 12m 16m 20m 40m

SCALE 1:400

SITE ADDRESS

MACEDON RANGES LOCATING SERVICE

POSTAL:
PO BOX 401
ROMSEY VIC 3434

EMAIL:
JAKE@MRLS.COM.AU

PHONE:
0403 222 537

DIAL BEFORE YOU DIG www.1100.com.au

CERTIFIED LOCATOR www.dbydiocator.com

THIS PLAN DOES NOT REPLACE DIAL BEFORE YOU DIG PLANS

WARNING

ACCURACY OF UNDERGROUND SERVICES INFORMATION

UNDERGROUND SERVICES SHOWN ON THIS PLAN HAVE BEEN LOCATED TO THE QUALITY LEVEL INDICATED IN THE LINE TYPE DESCRIPTOR. THE LOCATION AND DEPTHS STATED SHOULD BE TREATED AS APPROXIMATE AND CAN ONLY BE VERIFIED VIA PROVING METHODS (MANUAL EXPOSURE/NON-DESTRUCTIVE DIGGING; QL-A) OF WHICH, UNLESS OTHERWISE AGREED UPON, IS THE RESPONSIBILITY OF THE CONTRACTOR.
THERE IS NO GUARANTEE ALL SERVICES THAT EXIST IN THE AREA COVERED ON THIS PLAN ARE SHOWN.

GDA/MGA2020 ZONE 55
DRAWN: J. SUTHERLAND
DATE OF SURVEY: 12/10/2022
ORIGINAL SHEET SIZE: A3
SHEET NUMBER 1 0F 1